



Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910 1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY Eco Stripe White and Colors	<i>Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.</i>
---	---

Section I

Manufacturer's name US Specialty Coatings	Emergency Telephone Number 404-408-0401
Address (Number, Street, City, State and ZIP Code) 1000 McFarland 400 Blvd Alpharetta, GA 30004	Telephone Number for Information 770-740-8549
	Date Prepared 01/27/11
	Signature of Preparer (optional)

Section II—Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Aliphatic 108-88-3		100ppm		1
Aromatic hydrocarbons		300ppm		.07

Section III—Physical/Chemical Characteristics

Boiling Point	212 +F	Specific Gravity (H ₂ O = 1)	1.23 Average
Vapor Pressure (mm Hg)		Melting Point	
Vapor Density (AIR = 1)	Heavier than air	Evaporation Rate (Butyl Acetate = 1)	
Solubility in Water	100 %		
Appearance and Odor	White and Mild Various Colors		

Section IV—Fire and Explosion Hazard Data

Flash Point (Method Used) TCC/PM deg > F 200	Flammable Limits	LEL	UEL
Extinguishing Media	Dry Chemical		
Special Fire Fighting Procedures	Keep Materials from heat, sparks, and open flames		
Unusual Fire and Explosion Hazards	Water should be used to cool containers.		



Section V—Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	
Incompatibility (<i>Materials to Avoid</i>)			
Hazardous Decomposition or Byproducts			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI—Health Hazard Data

Route(s) of Entry	Inhalation?	Skin?	Ingestion?
Health Hazards (<i>Acute and Chronic</i>)			
Carcinogenicity	NTP?	IARC Monographs?	OSHA Regulated?
Signs and Symptoms of Exposure			
Medical Conditions Generally Aggravated by Exposure			
Emergency and First Aid Procedures			
Inhalation: Remove person to fresh air Skin Contact: Wash with soap and water			
Eye Contact: Flush eyes with water for at least 15 minutes, contact Physician			

Section VII—Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled	Remove all sources of ignition and ventilate vapors. Absorb with an inert material
Waste Disposal Method	Dispose in accordance with Federal, State, and Local Regulations
Precautions to Be Taken in Handling and Storing	Close containers after each use. Avoid damage to containers to prevent spills.
Keep material from heat, sparks and open flames	
Other Precautions	

Section VII—Control Measures

Respiratory Protection		Adequate ventilation is required. Use a respirator in confined areas, approved by U.S. Bureau of Mines.
Ventilation	Local Exhaust	vapor concentration below T.V. and L.E.L.
	Mechanical (<i>General</i>)	Other
Protective Gloves	Requires for prolonged contact	Eye Protection Use eye protection sufficient to prevent eye contact
Other Protective Clothing or Equipment		
Work/Hygienic Practices		

DISCLAIMER

The information contained herein is based on data and information considered and believed to be accurate. US SPECIALTY COATINGS INC. makes no warranties expressed or implied and assume no responsibility for the accuracy or completeness of the data. US SPECIALTY COATINGS INC. further assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by this material. Such vendors or users assume all risks associated with the use of this material.